COMFORT DPC-10 / DPC-10A Series



- Digital Pressure Switch can completely replace and outperform the pressure gauge / the pressure switch on a pressure tank system or the pressure control device
- · Digital Pressure Switch is characterized by its accuracy and high resolution
- · Autonomous protection to equipment and system

APPLICATION









Domestic

Civil

Agricultural Industr

FEATURE













- · All time status display and LCD backlit for anytime view
- · Clearly indicating 3-color LED light for reporting Status
- Protection limiting maximum starts per hour, protecting the pump from high frequent cycling per hour
- · Lock screen function to prevent non-user modifying parameter settings
- · Protection adjustable restart delay 0~90 minutes, controlling the pump cycle rate
- · Delayed Shutdown function Prevention of overloading of maximum start
- Auto-restart in event of water shortage and resupply pressure when water source is available
- Resource-protection: Auto-shutdown in the event the maximum run time is exceeded: great for protecting against burst water pipe
- · Fast response to accuracy and setting
- · Anti-vibration, anti-jamming ability
- · Easy to connect the wires and install
- Reset IC installed permanent memory of setting will not lose setting even loss of power
- Able to work with three phase pumps with a contactor with required voltage to Digital Pressure Controller

MODEL SELECTION


| Model | Maximum Pressure | Enclosure Size | Port Material | |
|---------|------------------|----------------|---------------|--|
| DPC-10 | 10 BAR | 3" | NICKEL BRASS | |
| DPC-16 | 16 BAR | 3" | AISI 304 | |
| DPC-25 | 25 BAR | 3" | AISI 304 | |
| DPC-10A | 10 BAR | 3 1/2" | NICKEL BRASS | |

*All DPC series are able to adjust based on users' required parameters

TECHNICAL DATA

| Power Supply | 110~230Vac±10% 50/60hz | | |
|--|---|--|--|
| Pressure Connection | R 1/4" | | |
| Accuracy | ± 1% Tolerance | | |
| Overload Capacity | Tested to 1.5 x the rated pressure | | |
| Output of Relay | ON/OFF | | |
| Relay Capacity (Maximum Motor Size) | 110V up to 1HP (0.75kW) 230V up to 2HP (1.5kW) | | |
| Maximum Current | 12A | | |
| Sampling Rate | 5 times/second | | |
| Working Temperature | -10°~65°C | | |
| Ingress Protection | IP55 | | |
| Display Pressure Unit | bar, psi, kgf/cm² | | |
| Ph Level | 6-9 | | |

DIMENSION



MODE

| MODEL | Α | В | С | |
|---------|-----|----|----|---|
| DPC-10 | 96 | 77 | 46 | |
| DPC-16 | 96 | 77 | 46 | K |
| DPC-25 | 96 | 77 | 46 | |
| DPC-10A | 103 | 85 | 55 | |